

QXEP-MR16IN-S3

Powered By HID® Mercury™



FEATURES

- 16 programmable inputs; 2 programmable relay outputs
- AES 128/256 bit data encryption
- UL 294 recognized, CE compliant, FCC, RoHS
- Configurable input parameters
- Initiates commands by operator, by time schedules, or by events
- Allows for easy and compact clustering of up to 16 uniquely monitored devices
- RS-485 host connectivity



SERIAL I/O 16-INPUT INTERFACE PANEL

- **Open Architecture** – High performance, reliable platform enables use of hardware with HID Mercury OEM partners' software solutions.
- **Easy Expansion** – Adds functionality and flexibility to existing access control systems
- **Enhanced Security** – Embedded crypto memory chip and data at rest encryption provides secured layer of protection of sensitive data.3
- **Versatile Interoperability** – Same reliable interface and identical footprint as the EP Controllers, enabling seamless upgrades for existing deployments.



The new QXEP-MR Series 3 Serial Input/Output (SIO) modules, powered HID Mercury, enable system expansion of QXEP intelligent controllers as part of HID Mercury's distributed architecture. The enhanced modules offer an improved processor and increased memory, plus feature an embedded crypto memory chip that provides a secured layer of encryption to onboard sensitive data. Built on the HID Mercury open platform, Series 3 modules provide the necessary flexibility for partners and end customers to choose the controller configuration that best fits their needs.

The QXEP-MR16IN can be used for a variety of applications, including status annunciation and alarm monitoring applications such as lighting, heating/cooling, door and elevator control. Devices can also be activated by the condition of selected system devices, either locally or regionally, without host intervention.

The panel is dedicated to point control and monitoring, enabling customers to support 16 general-purpose input circuits. The circuits can be individually set for sensitivity ranges, timing parameters (normally-open

or normally-closed operations) and end-of-line resistance values. They can also be declared supervised and non-supervised. Two programmable relay outputs are configurable for fail-safe or fail-secure operation, supporting "On," "Off," "Pulse" and "Repeating Pulse" commands.

The QXEP-MR16IN Series 3 is powered by the latest generation door interface module for HID Mercury intelligent controllers, the platform of choice for customers seeking open architecture access control solutions.

Application Notes

The QXEP-MR16IN is an essential component that supports Mercury's flexible, building-block approach to access control system design. The QXEP-MR16IN provides the capacity to link, control and respond to an array of sensors. With its RS-485 connectivity, the QXEP-MR16IN can be clustered or distributed to best suit each installation environment.

QXEP-MR16IN-S3 Controller, Powered by HID® Mercury™

Primary Power	12-24 VDC +/- 10%, 1100mA maximum
Host Communication	RS-485, 2-wire, 4,000' (twisted pair with shield, Belden 9841)
Inputs	16 General Purpose: Programmable circuit type 2 Dedicated: Tamper and Power Monitor
Output Relays	Two Form-C Relays: Normally open contact (NO): 5A @ 30 VDC resistive Normally closed contact (NC): 3A @ 30 VDC resistive
Dimensions	6.0" W x 8.0" L x 1.0" H (152mm W x 203mm L x 25mm H)
Temperature	Storage: -55° - 85° C Operational: 0° - 70° C
Humidity	5 to 95% RHNC
Product Compliance	UL294 Recognized, FCC Part 15 Class A, CE Compliant, RoHS (2011/65/EU & 2015/863), EU REACH (1907/2006), California Proposition 65

